

Manual Total Station

Zoom20 Pro Series



Easy Connectivity

- USB Memory Stick
- Fast & Easy Data Transfer
- Plug 'n Play Technology



Superior Display

- Largest 8 Line Display
- Highest Resolution in Class
- Graphical User Guidance



Performance, Robustness

- 400 m Non-Prism Range
- Coaxial Visible Laserbeam
- Sealed Durable Housing

Zoom20 Pro Series

At GeoMax we understand that you work in demanding environments and require excellent price-to-performance without compromising quality, that's why we build products that "work when you do".



The GeoMax Zoom20 Pro Manual total station includes an environmentally protected USB port that allows fast, simple and reliable data transfer between the instrument and your PC, even to other total stations.

Together with an extra large high-resolution display the easy-to-use graphical interface makes regular tasks like stake-out easier and more productive than ever before.

Zoom20 Pro accXess	Distance measurement on reflector
Zoom20 Pro accXess2	Distance measurement on reflector and 250m reflectorless*
Zoom20 Pro accXess4	Distance measurement on reflector and 400m reflectorless*

Angle measurements

Accuracy	2" (0.6 mgon), 3" (0.9 mgon), 5" (1.5 mgon), 7" (2 mgon),
Display resolution	1" (0.1 mgon)
Method	Absolute, continuous, diametrical
Compensation	Quadruple axis

Distance measurements

Prism	3,500 m / 2 mm + 2 ppm
Reflectorless	3 mm + 2 ppm
Footprint	8 x 20 mm**

Physical specifications

Weight	5.1 kg (incl. battery & tribrach)
Operating temp.	-30°C to 50°C***
Protection class	IP54 dust- and waterproof
Humidity	95 %, non-condensing

Interface

Keyboard	Full alphanumeric
Display	High resolution (280x160 pixel), 8 lines x 30 characters, illuminated
Data recording	Internal memory 50,000 pts
Interface	USB, serial & external power
Removable memory	USB memory stick

Power supply

Internal battery	Removable Li-Ion 4.4 Ah / 7.4 V
Operating time	36 h (continuous angle), 9 hours (continuous distance measurement every 30 s)

Plummet

Type	Laser point, adjustable brightness
Accuracy	1.5 mm at 1.5 m instrument height

Operating system

Windows®	Embedded CE
----------	-------------

* Optimal conditions to Kodak Grey Card (90% reflectivity)

** At 50 m distance

*** Optional tested polar version, standard -20°C to 50°C

All trademarks and trade names are those of their respective owners.

Distance meter (Reflector Mode): Laser class 1 in accordance with IEC 60825-1 resp. EN 60825-1; **Laser plummet:** Laser class 2 in accordance with IEC 60825-1 resp. EN 60825-1, **Distance meter (Reflectorless Mode accXess™):** Laser class 3R in accordance with IEC 60825-1 resp. EN 60825-1



Copyright GeoMax AG.
Illustrations, descriptions and technical specifications are not binding and may change.
XI.MMXIII / 808083en